

REMOTE ACCESS FOR LEVEL DATA LOGGERS

SL960-GSM

COMPACT & ROBUST

BATTERY POWERED

TRI-BAND GSM

www.signatrol.com

ONLINE CONNECTION TO THE DATA LOGGER

SEND SMS MESSAGES

INTRODUCTION

The SL960-GSM interface connects directly to the SL964 series data loggers and allows operators to dial in to the data logger and extract current level, temperature and conductivity as well as download all stored information.

The software allows automatic download of data from single or groups of data loggers with password protection if required.

Specification

GSM Engine	Triband
GSM Frequencies	GSM 900MHz, GSM 1800MHz, GSM 1900MHz
Transmission Power	Class 4 (2W) at EGSM900, class 1 (1W) at GSM 1800, GSM 1900
Transfer Rate	9600 Baud
Housing	Aluminium ALMgSil Chromated
Antenna Cover	Ertalyte Tx (PET) light grey
Battery	3.6V Lithium (D Size)
Battery Life	Approximately 1.5 Years at 4 downloads per month
Temperature Range	-20°C to +55°C (-4°F to +131°F)
PC Requirements	PC or laptop running Windows 98SE, 2000 or XP



Signatrol.com
Data Logging Solutions

ORDER CODE

SL960-GSM

GSM Communication Module

Mythe Barns Business Park,
Tewkesbury, Gloucestershire, GL20 6EA
Telephone: +44 (0)1684 299 399 Fax: +44 (0)1684 299 375 Email: sales@signatrol.com